## MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174 IDENTITY AND DISTRIBUTOR'S INFORMATION HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-8 IFPA Reting: Health-2; Flammebility-3; Resctivity-0; Special-DOT Hazard Classification: ORM-D Manufactured For. Bonded Logic, Inc. identity (trade name as used on label): Address: Address: 411 E. Ray Rd., Chandler, AZ Sticky Stuff Revision- 11 MSDS Number: A00315 480-812-9114 Prepared By: IB/TR EMERGENCY RESPONSE NUMBER: Date Prepared: 10/28/05 Information Calls: (770)422-2071 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION OSHA PEL ACGIH Cardnogen SARA COMPONENTS-CHEMICAL NAMES AND COMMON NAMES CAS Number HLLIST Ref. Source \*\* Hazardous Components 1% or greater; Carcinogens 0.1% or greater) TLV (ppm) (ppm) 67-64-1 No 1000 750 d HEPTANE 142-82-5 No 500 400 d ISOBUTANE / PROPANE BLEND 75-28-5 800 800 No d 74-98-6 No 1000 1000 d SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS Bolling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.853 /apor Pressure: PSIG @ 70°F (Aerosols): Max.BD apor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A = 1): N/E Vapor Density (Air = 1): N/E Evaporation Rate ( Water Reactive: No colubility in Water: Partial Appearance and Odor: Strew colored liquid with ketone solvent odor. SECTION 3 - FIRE AND EXPLOSION HAZARD DATA FLAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume: EXTREMELY FLAMMABLE NÆ %LEL:N/E % UEL: NE SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Use LASH POINT AND METHOD USED (non-serosols): water fog to cool containers to prevent rupturing & exploding containers. Provide shielding for personnel. EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water. Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130 F or the container may rupture. SECTION 4 - REACTIVITY HAZARD DATA HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR STABILITY [X] STABLE [ ] UNSTABLE ncompatibility (Mat. to avoid): Strong oxidizing agents. Conditions to Avoid: Open flame, welding arcs, heat, sparks. Hazardous Decomposition Products: Carbon dioxide, carbon monoxide. SECTION 5 - HEALTH HAZARD DATA PRIMARY ROUTES OF ENTRY: [X]INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS ACUTE EFFECTS Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible inconsciousness or aaphyxiation. Skin Contact: Irritation due to defatting of skin. ye Contact: Initation. ngestion: Possible chemical pneumonitis if aspirated into lungs. CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation of solvents may cause brain and other nervous system damage. Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions. EMERGENCY FIRST AID PROCEDURES Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention. ikin Contact: Wash with soap and water. If irritated, seek medical attention. Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention. SECTION 6 - CONTROL AND PROTECTIVE MEASURES Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode. Eye Protection: Safety glasses recommended. Protective Gloves: Neoprene. Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV. Other Protective Clothing & Equipment: None Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing. SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE Steps To Be Taken if Material is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER. Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without werranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Date Only